

SHOWERJET ONE-PIECE, HIGH-PRESSURE

SHOWER NOZZLES

OVERVIEW: SHOWERJET ONE-PIECE, HIGH-PRESSURE NOZZLES

Ideal for: easy replacement of ShowerJet and most other manufacturer showers

- Consolidated nozzle design eliminates the separate nut and gasket. All-in-one design saves time during installation and removal
- Faster and easier installation into the header using a 3/8" (9.5 mm) hex wrench
- Available in a variety of body lengths
- Powerful solid stream spray from .02 to 1.12 gpm (.08 to 4.24 lpm)
- Operating pressures up to 800 psi (55 bar)

ONE-PIECE, HIGH-PRESSURE NOZZLE OPTIONS



73196 & 73327

Solid stream spray pattern
 Ruby orifice for longer wear life
 Integral lock rings



37337, 38553 & 39468

Solid stream spray pattern
 Stainless steel orifices

QUICK REFERENCE GUIDE

Model Standard (Metric)	Connection Thread Size in. (mm)	Flow Rate Range gpm (lpm)	Materials
73196 (M73196)	1-3/16"-18 (M30 x 1.5)	.02 to 1.12 gpm (.08 to 4.24 lpm)	316 stainless steel body with synthetic ruby orifice
73327 (M73327)	1-1/4"-18 (M32 x 1.5)		
37337 (M37337)	1-3/16"-18 (M30 x 1.5)		316 stainless steel body and orifice
38553 (M38553)	1-1/4"-18 (M32 x 1.5)		
39468	1-3/8"-12		

FOR DETAILED NOZZLE PERFORMANCE DATA, SEE

- Standard Units
- Metric Units

PERFORMANCE DATA

SHOWER NOZZLES
SHOWERJET ONE-PIECE, HIGH-PRESSURE






STANDARD UNITS

PERFORMANCE DATA
SOLID STREAM SPRAY: 73196, 73327, 37337, 38553, 39468

Spray Angle at 60 psi	Capacity Size	Equiv. Orifice Dia. (in.)	Flow Rate Capacity (gallons per minute)				
			20 psi	40 psi	100 psi	250 psi	800 psi
0° (solid stream)	00003	.015	.02	.03	.05	.08	.13
	00005	.020	.04	.05	.08	.13	.22
	00008	.025	.06	.08	.13	.20	.36
	00011	.030	.08	.11	.17	.28	.49
	00015	.035	.11	.15	.24	.38	.67
	00020	.040	.14	.20	.32	.50	.89
	00025	.045	.18	.25	.40	.63	1.12

Highlighted column shows the rated pressure.

DIMENSIONS

Nozzle	Nozzle Type	Thread Size	L (in.)	A (in.)	D (Dia.) (in.)
	73196-A	1-3/16"-18 or M30 x 1.5	0.66	0.27	1.19
	73196-B		0.63	0.24	
	73196-C		0.73	0.34	
	73196-D		0.60	0.21	
	73327-A	1-1/4"-18 or M32 x 1.5	0.66	0.27	1.25
	73327-B		0.63	0.24	
	73327-C		0.73	0.34	
	73327-D		0.60	0.21	
	39468-A	1-3/16"-18 or M30 x 1.5	0.76	0.27	1.38
	39468-B		0.73	0.24	
	39468-C		0.83	0.34	
	39468-D		0.70	0.21	
	37337-A	1-3/16"-18 or M30 x 1.5	0.66	0.27	1.19
	37337-B		0.63	0.24	
	37337-C		0.73	0.34	
	37337-D		0.60	0.21	
	38553-A	1-1/4"-18 or M32 x 1.5	0.66	0.27	1.25
	38553-B		0.63	0.24	
	38553-C		0.73	0.34	
	38553-D		0.60	0.21	