

FEATURES AND BENEFITS

UNIJET NOZZLES

- Deliver a wide, uniform flat spray pattern




QUICK REFERENCE GUIDE

Tip Type	Connection	Connection Size (in.)	Materials
L	M or F	1/8, 1/4, 3/8	Brass (none), Stainless steel (SS)
P	M or F		
Q	M or F		
R	M or F		
U	M or F		
V	M or F		

PERFORMANCE DATA

Inlet Conn. (in.)	Tip Type	Width of slot in. (mm)	Capacity scfm (Nlpm)				Coverage at 6" (150 mm)	
			10 psi (.7 bar)	25 psi (2 bar)	50 psi (4 bar)	100 psi (6 bar)	10 psi (1 bar)	50 psi (4 bar)
1/8, 1/4, 3/8 (M or F)	L	.008 (.20)	.60 (17)	1.3 (41)	2.1 (68)	3.6 (93)	10 (275)	16.5 (419)
	P	.013 (.33)	1.2 (34)	2.0 (63)	3.1 (101)	5.4 (140)	5.5 (152)	10 (254)
	Q	.023 (.58)	2.2 (62)	3.9 (123)	6.2 (201)	10.7 (278)	8.5 (228)	13 (330)
	R	.045 (1.1)	3.9 (110)	6.4 (207)	11.0 (357)	19.0 (493)	6 (158)	9.5 (241)
	U	.045 (1.1)	6.3 (178)	11.0 (354)	18.5 (595)	31 (807)	10.5 (275)	14.5 (368)
	V	.091 (2.3)	12.5 (354)	23 (724)	37 (1184)	61 (1591)	9 (238)	13.5 (343)

DIMENSIONS AND WEIGHTS

	Nozzle Type	A in. (mm)	B in. (mm)	Weight oz. (kg.)
	T + Tip	1-13/16 (48)	13/16 (21)	2-1/4 (.06)
	TT + Tip	1-7/8 (48)	13/16 (21)	2-1/4 (.06)

Based on largest/heaviest version of each type.

ORDERING INFORMATION

UNIJET BLOW-OFF NOZZLE

Inlet Conn.	Body Type	-	Material	+	Tip Type	-	Material
-------------	-----------	---	----------	---	----------	---	----------

Example: 1/4 - T - SS + L - SS

BSPT connections require the addition of a "B" prior to the nozzle body inlet connection.

UNIJET BLOW-OFF TIP ONLY

Tip Prefix	Tip Type	-	Material
------------	----------	---	----------

Example: TB - L - SS

Material Code

(none) = Brass

SS = Stainless steel