

YMF MINIFOGGER® III

- High quality, cost-efficient dry fog with drop sizes seven to ten microns
- Compact design of 4.5" (115 mm) tall ideal for humidification applications with limited space
- Can be easily installed on a header, on a wall or on a ceiling
- Available with up to four stainless steel spray nozzle set-ups, each with automatic spray pattern alignment
- Choice of spray set-ups provide flow rates ranging from 0.24 to 1.22 gph (0.9 to 4.6 l/hr)
- 0.46 lbs. (210 g) for single spray set-up type; 0.55 lbs. (250 g) for multiple four set-up types
- Body, retainer cap and tank constructed of corrosion-resistant polypropylene with stainless steel air and water inlet connections
- Materials compatible with deionized water
- Easy to maintain – no tools required



**PERFORMANCE DATA:
YMF MINIFOGGER III**

*At the stated pressure in psi.

Spray Set-up No.	Air Capacity (standard cubic feet per minute)*			Flow Rate Capacity (gallons per hour and liters per hour)*			Sauter Mean Dia. (µm)		
	36 psi	44 psi	58 psi	36 psi	44 psi	58 psi	36 psi	44 psi	58 psi
SU1.0N	1.1	1.2	1.6	.24	.26	.29	8.5	7.6	6.7
SU2.5N				.61	.66	.69	9.6	8.5	7.6
SU3.0N				.74	.79	.85	9.8	9.0	8.4
SU4.5N				1.06	1.14	1.22	12.2	11.6	10.8

The standard MiniFogger III has four spray set-ups. Single spray set-ups are available. Contact your local representative for more information.

PLACING YOUR ORDER

Call 1.800.95.SPRAY for applications assistance or to place an order.



YMF MINIFOGGER® III

- High quality, cost-efficient dry fog with drop sizes seven to ten microns
- Compact design of 4.5" (115 mm) tall ideal for humidification applications with limited space
- Can be easily installed on a header, on a wall or on a ceiling
- Available with up to four stainless steel spray nozzle set-ups, each with automatic spray pattern alignment
- Choice of spray set-ups provide flow rates ranging from 0.24 to 1.22 gph (0.9 to 4.6 l/hr)
- 0.46 lbs. (210 g) for single spray set-up type; 0.55 lbs. (250 g) for multiple four set-up types
- Body, retainer cap and tank constructed of corrosion-resistant polypropylene with stainless steel air and water inlet connections
- Materials compatible with deionized water
- Easy to maintain – no tools required



PERFORMANCE DATA:
YMF MINIFOGGER III

*At the stated pressure in bar.

Spray Set-up No.	Air Capacity* (liters per minute)			Flow Rate Capacity* (liters per hour)			Sauter Mean Dia. (µm)		
	2.5 bar	3 bar	4 bar	2.5 bar	3 bar	4 bar	2.5 bar	3 bar	4 bar
SU1.0N	30	35	45	.9	1.0	1.1	8.5	7.6	6.7
SU2.5N				2.3	2.5	2.6	9.6	8.5	7.6
SU3.0N				2.8	3.0	3.2	9.8	9.0	8.4
SU4.5N				4.0	4.3	4.6	12.2	11.6	10.8

The standard MiniFogger III has four spray set-ups. Single spray set-ups are available. Contact your local representative for more information.

PLACING YOUR ORDER

**Call 1.630.665.5000 for applications assistance
or to place an order.**