



- FOR FLOWS UP TO 0.7 G.P.M.
- FOR PRESSURES UP TO 250 P.S.I.
- THREADED VALVE SEAT PREVENTS VALVE SEAT FROM FALLING OUT WHEN CHANGING THE SPRAY TIP.
- TAPERED NEEDLE STEM HEAD AND STOP ADJUSTING NUT PROVIDE METERED FLOW CAPABILITIES.
- TEFLON PACKINGS CAN BE TIGHTENED TO PREVENT WEEPING OF LIQUIDS.
- TRIGGER GUARD HELPS PREVENT BUMPING OF TRIGGER AND ACCIDENTAL GUN DISCHARGE.
- FOUR-FINGER TRIGGER FOR EASE OF OPERATION.
- SCREW FOR GROUND WIRE ATTACHMENT.
- FOR INTERCHANGEABLE SPRAY TIPS, SEE THE INDUSTRIAL SPRAY PRODUCTS CATALOG.
- SPRAY GUNS TO HANDLE FLOW RATES GREATER THAN 0.7 GPM ARE AVAILABLE UPON REQUEST.

DESCRIPTION:

No. AA23L-45885-7676-__ OR
 No. AA23L-45885-7676-__-SS
GUNJET® SPRAY GUN
 (WITH EXTENSION & SHUT-OFF)



Spraying Systems Co.®

Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No.

Ref.

Data Sheet No.

45885

SHEET 2 OF 2